



Emergency Telephone
(516) 249-9000

120 RT. 110, P.O. BOX 117, FARMINGDALE, N.Y. 11735

SUBSTANCE DATA SHEET

INSTR. OUR WORKERS TO HANDLE THIS PRODUCT PROPERLY

FIRST AID
Inhalation - Remove to fresh air
Eyes - Flush with water 15 minutes
Skin - Wash affected area with soap and water
Internal - Do not induce vomiting, call physician

FIRE HAZARD
Extinguishing Media - Foam, Dry Chemical, CO2
Use air supplied rescue equipment in enclosed area

STORAGE PRECAUTIONS
Store in cool, dry, environment, keep away from open flame

SPILL INFORMATION
Absorb on clay and sweep up

WASTE DISPOSAL
Incineration
Carbon Monoxide may form on incomplete combustion

NAME: DSW Duct Sealer
TYPE: Acrylic Emulsion
APPLICATION: Duct Sealer, Non-Fla-

ISSUE DATE: 1-31-86

PHYSICAL DATA
pH @ 25 C
Viscosity, Brookfield
Weight Per Gallon
Storage Life at 70 F

7.5-8.5
340M-400M CPS RVP 7/2 25 C
10.0-10.4 Lbs.
6 Months

SIGNAL WORD
Not applicable.

HAZARDOUS INGREDIENTS
Not applicable.

STATEMENT OF HAZARDS

This material has not been listed under subpart H (Hazardous Material) or subpart (Toxic Substances) of part 1910 Regulation, 29 CFR-19

HANDLING PRECAUTIONS
Not applicable.

PERSONAL PROTECTION

No special protective equipment needed.

DISCLAIMER
The information and recommendations contained herein are offered as a service to our customers, but are not intended to represent the safe use of any product. The user must exercise caution and use proper safety practices. The information and recommendations are based on the best information available at the time of preparation of this document. The user must exercise caution and use proper safety practices. The information and recommendations are based on the best information available at the time of preparation of this document.

226